


### Surface Mount General Purpose Silicon Rectifiers

Parameter	Value	Unit
$V_{RRM}$	50~1000	V
$I_{F(AV)}$	1.0	A



#### Features

- For surface mounted applications
- Low profile package
- Glass passivated chip junction
- Ideal for automated placement

#### Applications

- For use in general purpose rectification in power supplies, inverters, converters, and as freewheeling diodes for consumer and telecommunications applications.

### Absolute Maximum Ratings and Characteristics (at $T_J = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	1N4001L	1N4002L	1N4003L	1N4004L	1N4005L	1N4006L	1N4007L	Unit
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at $T_c = 125^\circ\text{C}$	$I_{F(AV)}$	1.0							A
Peak Forward Surge Current 8.3ms Single Half Sine Wave Superimposed on Rated Load	$I_{FSM}$	30							A
Maximum Instantaneous Forward Voltage at 1A	$V_F$	1.1							V
Maximum DC Reverse Current $T_a=25^\circ\text{C}$ at Rated DC Blocking Voltage $T_a=125^\circ\text{C}$	$I_R$	5 50							$\mu\text{A}$
Typical Junction Capacitance (1)	$C_j$	8(TYP.)							pF
Typical Thermal Resistance (2)	$R_{\theta JA}$	90							$^\circ\text{C}/\text{W}$
Operating and Storage Temperature Range	$T_j, T_{stg}$	-55 ~ +150							$^\circ\text{C}$

#### Notes:

1. Measured at 1 MHz and applied reverse voltage of 4 V D.C
2. P.C. B . mounted with 2 .0" X 2 .0" (5 X 5 cm) copper pad areas.

## Typical characteristics

Fig.1 Forward Current Derating Curve




Fig.2 Typical Instantaneous Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance






Fig.5 Maximum Non-Repetitive Peak Forward Surge Current




### Package Outlines

Plastic surface mounted package; 2 leads



### The recommended mounting pad size



### Marking

Type number	Marking code
1N4001L	A1
1N4002L	A2
1N4003L	A3
1N4004L	A4
1N4005L	A5
1N4006L	A6
1N4007L	A7

**\*Important Usage Information and Disclaimer**

The specifications of Zhuhai Hypersemi Co., Ltd. products are not guarantees of product characteristics. They reflect typical performance expected in standard applications, which may vary with specific uses. Users must conduct prior testing for their applications and make necessary adjustments.

Users are responsible for the safety of applications utilizing our products and must implement adequate safety measures to prevent physical injury, fire, or other risks in case of product failure. It is the user's duty to ensure that application designs comply with all applicable laws and standards. Our products must not be used in any applications where a product failure could reasonably result in personal injury, unless specifically authorized in a signed document by Zhuhai Hypersemi Co., Ltd.

No representations or warranties are made regarding the accuracy or completeness of this information, including any claims of non-infringement of third-party intellectual property rights. Zhuhai Hypersemi Co., Ltd. assumes no liability for any applications or uses of its products and does not grant any licenses to its intellectual property rights or those of others. We also make no claims regarding non-infringement of third-party intellectual property rights that may arise from applications.

Due to technical requirements, our products may contain hazardous substances. For details, please contact your nearest sales office. This document replaces all previous information and may be updated. We reserve the right to make changes.